

# Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 12/05/2022

Reviewed on 12/05/2022

## \* 1 Identification

- **Product Identifier**
- **Trade Name: SpeedyDry**
- **Relevant identified uses of the substance or mixture and uses advised against:**  
No further relevant information available.
- **Product Description:** Ink Additive
- **Application of the substance / the mixture:** To be added to conventional offset inks.
- **Details of the Supplier of the Safety Data Sheet:**
- **Manufacturer/Supplier:**  
Genesis, LLC  
256 West Trade Street  
Burlington, NC U.S.A  
Phone: 1-336-261-0170
- **Emergency telephone number:**  
800-424-9300 (Chemtrec U.S. & Canada Calls)  
+32 14 58 45 45 (24h/24h) Information centre on dangerous goods (BIG)

## \* 2 Hazard(s) Identification

- **Classification of the substance or mixture:**



Health hazard

Sensitization - Respiratory 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Specific Target Organ Toxicity - Repeated Exposure 1	H372	Causes damage to the respiratory system through prolonged or repeated exposure.
Aspiration Hazard 1	H304	May be fatal if swallowed and enters airways.



Skin Irritation 2	H315	Causes skin irritation.
Eye Irritation 2A	H319	Causes serious eye irritation.
Sensitization - Skin 1	H317	May cause an allergic skin reaction.
Specific Target Organ Toxicity - Single Exposure 3	H335-H336	May cause respiratory irritation. May cause drowsiness or dizziness.

- **Label elements:**
- **Hazard pictograms:**



- **Signal word:** Danger

(Contd. on page 2)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 12/05/2022

Reviewed on 12/05/2022

**Trade Name: SpeedyDry**

- **Hazard-determining components of labeling:**

Cobalt Neodecanoate  
Manganese Neodecanoate  
Distillates (petroleum), hydrotreated middle

- **Hazard statements:**

H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H317 May cause an allergic skin reaction.  
H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.  
H372 May cause damage to the respiratory system through prolonged or repeated exposure.  
H304 May be fatal if swallowed and enters airways.

- **Precautionary statements:**

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P260 Do not breathe dust/fume/gas/mist/vapors/spray.  
P261 Avoid breathing dust/fume/gas/mist/vapors/spray.  
P264 Wash thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P271 Use only outdoors or in a well-ventilated area.  
P272 Contaminated work clothing must not be allowed out of the workplace.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P284 [In case of inadequate ventilation] wear respiratory protection.  
P301+P310 If swallowed: Immediately call a poison center/doctor.  
P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).  
P331 Do NOT induce vomiting.  
P302+P352 If on skin: Wash with plenty of water.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313 IF exposed or concerned: Get medical advice/attention.  
P312 Call a poison center/doctor if you feel unwell.  
P314 Get medical advice/attention if you feel unwell.  
P362+P364 Take off contaminated clothing and wash it before reuse.  
P332+P313 If skin irritation occurs: Get medical advice/attention.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313 If eye irritation persists: Get medical advice/attention.  
P342+P311 If experiencing respiratory symptoms: Call a poison center/doctor.  
P363 Wash contaminated clothing before reuse.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
P405 Store locked up.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Unknown acute toxicity:**

This value refers to knowledge of known, established toxicological or ecotoxicological values.  
26.9 % of the mixture consists of component(s) of unknown toxicity.

- **Classification system:** NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme

(Contd. on page 3)

# Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 12/05/2022


Reviewed on 12/05/2022

**Trade Name: SpeedyDry**

· **NFPA ratings (scale 0 - 4)**



· **HMS-ratings (scale 0 - 4)**



· **Hazard(s) not otherwise classified (HNOC):** None known

## \* 3 Composition/Information on Ingredients

· **Chemical characterization: Substance**

· **Description:** Mixture of substances listed below with non-hazardous additions.

· **Dangerous Components:**

CAS: 27253-31-2	Cobalt Neodecanoate ⚠ Sensitization - Respiratory 1, H334; Aspiration Hazard 1, H304; ⚠ Acute Toxicity - Oral 4, H302; Acute Toxicity - Dermal 4, H312; Acute Toxicity - Inhalation 4, H332; Skin Irritation 2, H315; Flammable Liquids 4, H227; Eye Irritation 2B, H320	2-10%
CAS: 8042-47-5	White mineral oil, petroleum	2-12%
CAS: 27253-32-3	Manganese Neodecanoate ⚠ Specific Target Organ Toxicity - Single Exposure 2, H371; Aspiration Hazard 1, H304; ⚠ Acute Toxicity - Oral 4, H302; Acute Toxicity - Inhalation 4, H332; Skin Irritation 2, H315; Eye Irritation 2A, H319; Flammable Liquids 4, H227	2-12%
CAS: 64742-46-7	Distillates (petroleum), hydrotreated middle ⚠ Aspiration Hazard 1, H304	2-12%
CAS: 25265-71-8 EINECS:246-770-3	Dipropylene Glycol ⚠ Flammable Liquids 3, H226; Specific Target Organ Toxicity-Repeated Exposure 1, H372; Aspiration Hazard 1, H304	≤1.0%
CAS: 136-52-7	cobalt(II) 2-ethylhexanoate ⚠ Acute Toxicity - Inhalation 3, H331; Acute Toxicity - Oral 4, H302; Acute Toxicity - Dermal 4, H312	≤.09%

· **Additional information:**

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

## \* 4 First-Aid Measures

· **Description of first aid measures**

· **General information:**

Symptoms of poisoning may occur after exposure to dust, fumes or particulates; seek medical attention if feeling unwell.

· **After inhalation:** In case of unconsciousness place patient stably in the side position for transportation.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 4)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 12/05/2022

Reviewed on 12/05/2022

### Trade Name: SpeedyDry

If skin irritation occurs, consult a doctor.

· **After eye contact:**

Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor.

If easy to do so, remove contact lenses if worn.

If eye irritation occurs, consult a doctor.

· **After swallowing:**

Immediately call a doctor.

If vomiting occurs, the head should be kept low so that the vomit does not enter the lungs (aspiration). Once the vomiting ceases, place the person in the recovery position with the legs slightly raised.

Never give anything by mouth to an unconscious person.

Do not induce vomiting without medical advice.

To prevent aspiration of swallowed product, lay victim on side with head lower than waist.

· **Information for doctor**

· **Most important symptoms and effects, both acute and delayed:** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed:**

No further relevant information available.

### \* 5 Fire-Fighting Measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** No further relevant information.

· **Special hazards arising from the substance or mixture:**

In certain fire conditions, traces of other toxic gases cannot be excluded.

Closed containers may explode when exposed to extreme heat.

· **Advice for firefighters**

· **Special protective equipment for firefighters:**

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

### \* 6 Accidental Release Measures

· **Personal precautions, protective equipment and emergency procedures:** Not required.

· **Environmental precautions:** Dilute with plenty of water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to section 13.

Ensure adequate ventilation.

Dispose of the collected material according to regulations.

· **Reference to other sections:**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· **PAC-1:**

	25265-71-8 Dipropylene Glycol	400 mg/m <sup>3</sup>
--	-------------------------------	-----------------------

· **PAC-2:**

	25265-71-8 Dipropylene Glycol	1,900 mg/m <sup>3</sup>
--	-------------------------------	-------------------------

· **PAC-3:**

	25265-71-8 Dipropylene Glycol	25000** mg/m <sup>3</sup>
--	-------------------------------	---------------------------

(Contd. on page 5)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 12/05/2022

Reviewed on 12/05/2022

**Trade Name: SpeedyDry**

### 7 Handling and Storage

- **Handling**
- **Precautions for safe handling:**  
Avoid contact with skin, eyes and clothing  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** Keep protective respiratory device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and receptacles:** Store in a cool, dry place.
- **Information about storage in one common storage facility:** Store away from oxidizing agents.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s):** No further relevant information available.

### \* 8 Exposure Controls/Personal Protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters:**
- **Components with occupational exposure limits:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the remaining constituents have no known exposure limits.

<b>27253-31-2 Cobalt Neodecanoate</b>	
OSHA PEL	Long-term value: 0.1 mg/m <sup>3</sup>
<b>8042-47-5 White mineral oil, petroleum</b>	
ACGIH TLV	Short-term value: 10 mg/m <sup>3</sup> Long-term value: 5 mg/m <sup>3</sup>
OSHA PEL	Long-term value: 5 mg/m <sup>3</sup>
<b>27253-32-3 Manganese Neodecanoate</b>	
OSHA PEL	Long-term value: 5 mg/m <sup>3</sup>
<b>25265-71-8 Dipropylene glycol</b>	
PEL	Long-term value: 2500 mg/m <sup>3</sup> , 450 ppm
REL	Long-term value: 300 mg/m <sup>3</sup> Ceiling limit value: 1900* mg/m <sup>3</sup> *15-min
TLV	Long-term value: 150 ppm
<b>136-52-7 cobalt(II) 2-ethylhexanoate</b>	
TLV	Long-term value: 0.02* mg/m <sup>3</sup> as Co, A3; *inhalable; DSEN; RSEN; BEI

- **Additional information:** The lists that were valid during the creation of this SDS were used as basis.
- **Exposure controls:**  
Use in well ventilated area. Observe Occupational Exposure Limits (OEL) and minimize the risk of inhalation of vapors or mists. Use mechanical or local exhaust ventilation.
- **Personal protective equipment**
- **General protective and hygienic measures:**  
The usual precautionary measures for handling chemicals should be followed.

(Contd. on page 6)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 12/05/2022

Reviewed on 12/05/2022

### Trade Name: SpeedyDry

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing and wash before reuse.  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.  
Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure, use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Select glove material based on penetration times, rates of diffusion and degradation.



Protective gloves

· **Material of gloves:**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material:**

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

· **Eye protection:**



Tightly sealed goggles

· **Body protection:**



Protective work clothing

· **Limitation and supervision of exposure into the environment:** None

## 9 Physical and Chemical Properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:

Liquid

Color:

Purple

· **Odor:**

Mild

· **Odor threshold:**

Not determined.

· **pH-value:**

Not available

· **Change in condition**

Melting point/Melting range:

Not determined.

Boiling point/Boiling range:

≥36 °C (≥96.8 °F)

(Contd. on page 7)

**Safety Data Sheet (SDS)**

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 12/05/2022

Reviewed on 12/05/2022

**Trade Name: SpeedyDry**

- **Flash point:** 96 °C (204.8 °F) (Pensky Martens Closed Cup)
- **Flammability (solid, gaseous):** Not applicable.
- **Ignition temperature:** Not applicable
- **Decomposition temperature:** Not determined.
- **Auto igniting:** Product is not self-igniting.
- **Danger of explosion:** Product does not present an explosion hazard.
- **Explosion limits:**
  - Lower:** 1.1 Vol %
  - Upper:** 6 Vol %
- **Vapor pressure @ 20 °C (68 °F):** ≤1.3 hPa (≤1 mm Hg)
- **Density @ 20 °C (68 °F):** 1 g/cm<sup>3</sup> (8.345 lbs/gal)
- **Relative density:** Not determined.
- **Vapor density:** <1 (Air=1)
- **Evaporation rate:** Not determined.
- **Solubility in / Miscibility with:**
  - Water:** Fully miscible.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
  - Dynamic:** Not determined.
  - Kinematic:** Not determined.
- **Solvent content:**
  - VOC content:** 0.00 %
  - Solids content:** 0.1 %
- **Other information:** No further relevant information available.

**10 Stability and Reactivity**

- **Reactivity:** No further relevant information available.
- **Chemical stability:** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:**  
Carbon dioxide and carbon monoxide may form when heated to decomposition.  
Cobalt oxides and manganese oxides.
- **Possibility of hazardous reactions:** No dangerous reactions known.
- **Conditions to avoid:** No further relevant information available.
- **Incompatible materials:** Strong oxidizing agents.
- **Hazardous decomposition products:** Irritant gases/vapors

**\*11 Toxicological Information**

- **Information on toxicological effects:**
- **Acute toxicity:**

<b>LD/LC50 values that are relevant for classification:</b>		
<b>8042-47-5 White mineral oil, petroleum</b>		
Oral	LD50	>5,000 mg/kg (Rat)

(Contd. on page 8)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 12/05/2022

Reviewed on 12/05/2022

**Trade Name: SpeedyDry**

<b>25265-71-8 Dipropylene glycol</b>		
Oral	LD50	>700 ml/kg (Rat)
Dermal	LD50	>200 ml/kg (Rabbit)

- **Primary irritant effect:**

- **On the skin:**

Irritant to skin and mucous membranes.  
May cause an allergic skin reaction.

- **On the eye:** Irritating effect.

- **Sensitization:**

Sensitization possible through inhalation.  
Sensitization possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful  
Irritant

The product can cause inheritable damage.

- **Carcinogenic categories:**

- **IARC (International Agency for Research on Cancer):**

Group 1 - Carcinogenic to humans  
Group 2A - Probably carcinogenic to humans  
Group 2B - Possibly carcinogenic to humans  
Group 3 - Not classifiable as to its carcinogenicity to humans  
Group 4 - Probably not carcinogenic to humans

27253-31-2	Cobalt Neodecanoate	2B
136-52-7	cobalt(II) 2-ethylhexanoate	2B

- **NTP (National Toxicology Program):**

None of the ingredients are listed.

- **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

### 12 Ecological Information

- **Toxicity:**

- **Aquatic toxicity:** Toxic to aquatic life

- **Persistence and degradability:** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential:** No further relevant information available.

- **Mobility in soil:** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Do not allow undiluted product or product that has not been neutralized to reach ground water, water course or sewage system.

- **Results of PBT and vPvB assessment:**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects:** No further relevant information available.

(Contd. on page 9)



## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 12/05/2022

Reviewed on 12/05/2022

**Trade Name: SpeedyDry**

### 13 Disposal Considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household waste. Do not allow product to reach sewage system. Observe all federal, state and local environmental regulations when disposing of this material.
- **Uncleaned packaging**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

### 14 Transport Information

- **UN-Number:**
- **DOT, ADR/ADN, ADN, IMDG, IATA** Non-Regulated Material
- **UN proper shipping name:**
- **DOT, ADR/ADN, ADN, IMDG, IATA** Non-Regulated Material
- **Transport hazard class(es):**
- **DOT, ADR/ADN, ADN, IMDG, IATA**
- **Class:** Non-Regulated Material
- **Packing group:**
- **DOT, ADR/ADN, IMDG, IATA** Non-Regulated Material
- **Environmental hazards:** Not applicable.
- **Special precautions for user:** Not applicable.
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:** Not applicable.
- **UN "Model Regulation":** Non-Regulated Material

### \*15 Regulatory Information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture:**
- **SARA (Superfund Amendments and Reauthorization):**

- **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

- **Section 313 (Specific toxic chemical listings):**

27253-31-2	Cobalt Neodecanoate
------------	---------------------

136-52-7	cobalt(II) 2-ethylhexanoate
----------	-----------------------------

- **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

- **Hazardous Air Pollutants**

27253-31-2	Cobalt Neodecanoate
------------	---------------------

136-52-7	cobalt(II) 2-ethylhexanoate
----------	-----------------------------

- **California Proposition 65:**

- **Chemicals known to cause cancer:**

None of the ingredients are listed.

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

(Contd. on page 10)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 12/05/2022

Reviewed on 12/05/2022

**Trade Name: SpeedyDry**

· <b>Chemicals known to cause reproductive toxicity for males:</b>	
None of the ingredients are listed.	
· <b>Chemicals known to cause developmental toxicity:</b>	
None of the ingredients are listed.	
· <b>New Jersey Right-to-Know List:</b>	
136-52-7	cobalt(II) 2-ethylhexanoate
· <b>New Jersey Special Hazardous Substance List:</b>	
None of the ingredients are listed.	
· <b>Pennsylvania Right-to-Know List:</b>	
136-52-7	cobalt(II) 2-ethylhexanoate
25265-71-8	Dipropylene glycol (isomer unspecified)
· <b>Pennsylvania Special Hazardous Substance List:</b>	
None of the ingredients are listed.	
· <b>Carcinogenic categories:</b>	
· <b>EPA (Environmental Protection Agency):</b>	
None of the ingredients are listed.	
· <b>IARC (International Agency for Research on Cancer):</b>	
Cobalt Neodecanoate	
Distillates (petroleum), hydrotreated middle	
Cobalt bis (2-ethylhexanoate)	
· <b>TLV (Threshold Limit Value established by ACGIH):</b>	
None of the ingredients are listed.	
· <b>NIOSH-Ca (National Institute for Occupational Safety and Health):</b>	
None of the ingredients are listed.	

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms:**· **Signal word:** Danger· **Hazard-determining components of labeling:**

Cobalt Neodecanoate

Stoddard solvent

Manganese Neodecanoate

Distillates (petroleum), hydrotreated middle

· **Hazard statements:**

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 12/05/2022

Reviewed on 12/05/2022

### Trade Name: SpeedyDry

- H372 Causes damage to the respiratory system through prolonged or repeated exposure.  
 H304 May be fatal if swallowed and enters airways.

#### Precautionary statements:

- P201 Obtain special instructions before use.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P260 Do not breathe dust/fume/gas/mist/vapors/spray.  
 P261 Avoid breathing dust/fume/gas/mist/vapors/spray.  
 P264 Wash thoroughly after handling.  
 P270 Do not eat, drink or smoke when using this product.  
 P271 Use only outdoors or in a well-ventilated area.  
 P272 Contaminated work clothing must not be allowed out of the workplace.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P284 [In case of inadequate ventilation] wear respiratory protection.  
 P301+P310 If swallowed: Immediately call a poison center/doctor.  
 P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).  
 P331 Do NOT induce vomiting.  
 P302+P352 If on skin: Wash with plenty of water.  
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.  
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P308+P313 IF exposed or concerned: Get medical advice/attention.  
 P312 Call a poison center/doctor if you feel unwell.  
 P314 Get medical advice/attention if you feel unwell.  
 P362+P364 Take off contaminated clothing and wash it before reuse.  
 P332+P313 If skin irritation occurs: Get medical advice/attention.  
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
 P337+P313 If eye irritation persists: Get medical advice/attention.  
 P342+P311 If experiencing respiratory symptoms: Call a poison center/doctor.  
 P363 Wash contaminated clothing before reuse.  
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
 P405 Store locked up.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

#### National regulations:

The product is not subject to be labelled according with the prevailing version of the regulations on hazardous substances.

**Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

#### Contact:

#### Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road  
 ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
 IMDG: International Maritime Code for Dangerous Goods  
 DOT: US Department of Transportation  
 IATA: International Air Transport Association  
 EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 12)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 12/05/2022

Reviewed on 12/05/2022

### Trade Name: SpeedyDry

ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
NFPA: National Fire Protection Association (USA)  
HMIS: Hazardous Materials Identification System (USA)  
VOC: Volatile Organic Compounds (USA, EU)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
NIOSH: National Institute for Occupational Safety and Health  
OSHA: Occupational Safety & Health Administration  
TLV: Threshold Limit Value  
PEL: Permissible Exposure Limit  
REL: Recommended Exposure Limit  
Flammable Liquids 3: Flammable liquids – Category 3  
Flammable Liquids 4: Flammable liquids – Category 4  
Acute Toxicity - Oral 4: Acute toxicity – Category 4  
Acute Toxicity - Inhalation 3: Acute toxicity – Category 3  
Skin Irritation 2: Skin corrosion/irritation – Category 2  
Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A  
Eye Irritation 2B: Serious eye damage/eye irritation – Category 2B  
Sensitization - Respiratory 1: Respiratory sensitisation – Category 1  
Sensitization - Skin 1: Skin sensitisation – Category 1  
Carcinogenicity 2: Carcinogenicity – Category 2  
Specific Target Organ Toxicity - Single Exposure 2: Specific target organ toxicity (single exposure) – Category 2  
Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3  
Specific Target Organ Toxicity - Repeated Exposure 1: Specific target organ toxicity (repeated exposure) – Category 1  
Aspiration Hazard 1: Aspiration hazard – Category 1

· \* **Data compared to the previous version altered.**